

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A dialog method for dialog between an operator of an aircraft and at least one system of the aircraft, comprising the steps of:

displaying on a display a plurality of windows, each at least one window including at least one responsive object ~~a plurality of responsive objects~~ respectively associated with one of multiple functions of the at least one system of the aircraft, each window including one default field on which a cursor arrives after moving from one window to another window;

moving the ~~[[a]]~~ cursor in a continuous manner on the display so as to designate a responsive object; ~~and~~

moving the cursor in a discrete manner on the display, responsive object by responsive object, so as to designate a responsive object; and

moving the cursor discretely from one window to another window in the plurality of windows.

Claim 2 (Original): The dialog method according to claim 1,  
wherein the step of moving the cursor in the continuous manner on the display is performed with a control ball on a mouse, and

wherein the step of moving the cursor in the discrete manner on the display is performed with an arrow key on a keyboard.

Claim 3 (Original): The dialog method according to claim 1, further comprising:  
activating a function associated with the responsive object designated by the step of moving the cursor in the continuous manner on the display, and

activating a function associated with the responsive object designated by the step of moving the cursor in the discrete manner on the display.

Claim 4 (Original): The dialog method according to claim 3,  
wherein the step of activating the function associated with the responsive object designated by the step of moving the cursor in the continuous manner on the display is performed with a key on a mouse, and

wherein the step of activating the function associated with the responsive object designated by the step of moving the cursor in the discrete manner on the display is performed with an Enter key on a keyboard.

Claims 5 and 6 (Canceled).

Claim 7 (Currently Amended): The dialog method according to claim 1 [[6]],  
wherein each default field includes one default responsive object.

Claim 8 (Currently Amended): The dialog method according to claim 1 [[5]],  
wherein the step of moving from said one window to said another window is performed with a Tab key on a keyboard.

Claim 9 (Original): The dialog method according to claim 1,  
wherein the step of moving the cursor in the discrete manner on the display is activated during an emergency mode of the aircraft.

Claim 10 (Original): The dialog method according to claim 1, further comprising the step of:

automatically moving the cursor to a responsive object via a single action by the operator.

Claim 11 (Original): The dialog method according to claim 1,  
wherein the step of moving the cursor in the continuous manner on the display is performed with a mouse and the step of moving the cursor in the discrete manner on the display is performed with a keyboard.

Claim 12 (Original): The dialog method according to claim 1,  
wherein the step of moving the cursor in the discrete manner on the display moves the cursor discretely on the display, responsive object by responsive object, in a cyclical manner.

Claim 13 (Original): The dialog method according to claim 1,  
wherein the display includes a plurality of displays, and  
wherein the method further includes the step of moving the cursor from one display to another display in the plurality of displays means.

Claim 14 (Currently Amended): The dialog method according to claim 13,  
~~wherein the at least one window includes a plurality of windows, each window being divided into a plurality of fields each including at least one responsive object, and~~  
wherein each display includes one default field situated on one of the plurality of windows, and on which the cursor arrives after moving from said one display to said another display.

Claim 15 (Original): The dialog method according to claim 13,  
wherein the cursor is moved from said one display to said another display via one of a  
key on a mouse and a key on a keyboard.

Claim 16 (Original): The dialog method according to claim 1,  
wherein the display includes eight displays, of which three displays are for a pilot of  
the aircraft, three other displays are for the copilot of the aircraft, and two displays are for  
common use by the pilot and copilot of the aircraft.

Claim 17 (Previously Presented): A dialog method for dialog between at least one  
operator of an aircraft and at least one system of said aircraft, comprising the steps of:

displaying on at least two interactive windows, each of said at least two interactive  
windows including at least one responsive object associated with one of a plurality of  
functions of said at least one system of said aircraft;

moving a cursor on said interactive windows in an actuatable manner so as to  
designate a responsive object;

moving the cursor on said interactive windows in a discrete manner, responsive object  
by responsive object, so as to designate a responsive object;

confirming said designated responsive object either in an actuatable manner or using  
at least one confirmation key; and

moving said cursor from window to window using an auxiliary displacement key.

Claim 18 (Previously Presented): The dialog method of claim 17, further comprising  
the step of moving said cursor directly onto a responsive object associated with a function  
using a function key.

Claim 19 (Previously Presented): The dialog method of claim 17, further comprising the step of displaying said cursor at a default location in a window after moving said cursor from one window to another window.

Claim 20 (Previously Presented): The dialog method of claim 18, further comprising the step of displaying said cursor at a default location in a window after moving said cursor from one window to another window.

Claim 21 (Previously Presented): The dialog method according to claim 1, further comprising the step of:

confirming the designated responsive object in an actuatable manner.

Claim 22 (Previously Presented): The dialog method according to claim 1, further comprising the step of:

confirming the designated responsive object using at least one confirmation key.

Claim 23 (Previously Presented): The dialog method according to claim 1, further comprising the step of moving said cursor directly onto a responsive object associated with a function using a function key.